



Installation Instructions – Terrazzo Precast Shower Floors & Mop Basins

FIAT
PRODUCTS™


DO NOT STACK OR STORE TERRAZZO FLAT




MONTEREY




SIERRA



GIBRALTAR



**ADAT, ADAW, WTR
WHEELCHAIR ACCESS**



MOP SERVICE BASIN


1. REMOVE CRATE AT INSTALLATION POINT. DO NOT ROCK TERRAZZO ON EDGES IN ORDER TO PREVENT DAMAGES TO CORNERS.
 2. CHECK ALL SIDES OF PRODUCT FOR TRANSPORTATION DAMAGES.
- A:** WIPE FACE OF THE TERRAZZO WITH A WATERED CLOTH.
B: AFTER WATER EVAPORATES, CHECK FOR CRACKS OR DAMAGE.

NOTE: FIAT PRODUCTS IS NOT RESPONSIBLE FOR SHOWER INSTALLATIONS ADHERING TO A.D.A. GUIDELINES. CHECK LOCAL AUTHORITY FOR CODE AND INSTALLATION REQUIREMENTS.


LEVEL PRODUCT CAREFULLY

- 2A.** ESTABLISH PROPER CLEARANCE BETWEEN UNIT AND WALL. PLACE A 1/2" LAYER OF MORTAR WHERE THE SHOWER FLOOR IS TO BE INSTALLED. THIS PROCEDURE IS REQUIRED BY FIAT TO PROVIDE SUPPORT OF THE UNIT IN CASE THE SUB FLOOR IS UNEVEN. LAYER OF GROUT SHOULD BE AT LEAST 1/4" THICK AND COVER ENTIRE AREA UNDER THE UNIT.
- 2B.** ADAT AND ADAW SHOWERS ARE FOR A.D.A. OR PHYSICALLY CHALLENGED USE. THE SHOWER ENTRY SHOULD BE NO MORE THAN 1/4" HIGHER THAN THE FINISHED FLOOR OF THE ROOM. THE ADAT SHOWER SHOULD BE INSTALLED INTO A RECESSED PIT 2 INCHES DEEP TO MEET CODE REQUIREMENTS.
- 2C.** IT IS RECOMMENDED THAT A FLOOR DRAIN AT OR NEAR THE ENTRANCE TO ALL ADAT, ADAW AND WTR SHOWER FLOORS BE INCLUDED.


DO NOT LIFT SHOWER BY FLANGE



REMOVE CRATE WITH CARE



DO NOT STAND ON END




RECOMMENDED
1/4" SPACE
BY FIAT



DOTTED AREA
IS FOR
SHOWER FLOOR




ADAT BASE INSTALLED IN PIT
For the Physically Challenged




FAILURE TO INSTALL TERRAZZO ON A 1/2" MORTAR BED WILL VOID WARRANTY.

WARNING


- 3.** DO NOT DROP UNIT OVER EXPOSED PIPE. IT IS ADVISABLE TO REMOVE DRAIN PIPE AND SET UNIT IN PLACE. INSERT PIPE THROUGH DRAIN IN FLOOR BACK INTO "P" TRAP.
- TIGHTEN METAL CONNECTIONS WITH AN INTERNAL PIPE WRENCH.
IF USING PLASTIC WASTE PIPE, FIT AND SOLVENT WELD.



DO NOT DROP
ON PIPE



REMOVE PIPE
FROM TRAP




REINSERT PIPE & TIGHTEN
WITH AN INTERNAL WRENCH

4A. METHOD OF DRAIN CONNECTION: METAL WASTE PIPE


USE OAKUM AND MOLTEN LEAD.

THIS LEAD CAULKED JOINT PERMITS LIMITED MOVEMENTS SUCH AS NORMAL STRUCTURAL SETTLEMENT WITHOUT LEAKAGE.



RECOMMENDED PROCEDURE

- A.** TAMP OAKUM TO 5/8" DEPTH
- B.** POUR MOLTEN LEAD
- C.** TAMP LEAD CAREFULLY



4B. METHOD OF DRAIN CONNECTION: PLASTIC WASTE PIPE

WHEN USING PLASTIC WASTE PIPE, IT IS NECESSARY TO USE THE QDC QUICK DRAIN CONNECTOR.


INSTALL PIPE THROUGH RECEPTOR.

LUBRICATE QDC CONNECTOR WITH SOAP, STRETCH QDC CONNECTOR OVER PIPE WITH LETTERS FACING UP.

TAMP CONNECTOR WITH A HAMMER AND PIECE OF WOOD. WORK AROUND CONNECTOR WITH A SERIES OF BLOWS UNTIL IT BOTTOMS. TOP OF PIPE SHOULD BE EVEN WITH TOP OF CONNECTOR.




RECOMMENDED PROCEDURE QDC CONNECTOR

- A.** INSTALL QDC CONNECTOR
- B.** TAMP QDC TO BOTTOM
- C.** TEST CONNECTION FOR LEAKS
- D.** SNAP STRAINER IN PLACE



WARNING: MODELS WITH TILING FLANGE OPTIONS

- 5A.** DO NOT LET ROUGH WALL MATERIAL OVERLAP FLANGE.
- 5B.** DO NOT ATTACH FLANGE TO BUILDING.
- 5C.** LET FINISHED WALL (TILE, ETC) OVERLAP AND REST ON SHOULDER.



Sealers - New Installations

Immediately following installation of a new floor or thorough cleaning of an older floor, the floor can be sealed with a penetrating sealer. Such sealers are available at paint or tile stores and **must** state that they are approved for use on Terrazzo products. Sealers are not permanent and can be reapplied (after a thorough cleaning) approximately once a year, or as recommended by the manufacturer of the sealer.

RECOMMENDED CLEANING & MAINTENANCE PROCEDURES FOR TERRAZZO PRECAST SHOWER FLOORS AND MOP SERVICE BASINS

Regular Cleaning

To maintain the original terrazzo surface appearance, clean regularly with a liquid detergent such as Joy, Liquid Ajax, or Spic n Span (for the latter, prepare a solution containing 1/2 cup of Spic n Span in a gallon of water). Scrub with a stiff bristled, non-metallic scrub brush and then rinse thoroughly.

NOTE: Do not use any acid (ie, muratic) or cleaning agents that contain acid.

Special or Unusual Conditions

- | | |
|---------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| A. Scum on Surface caused by soap, makeup, etc.: | Use a cleaning powder, such as Ajax, plus lots of elbow grease. |
| B. Surface cleaning: | Heel marks, plaster, etc. may require abrasive removal. This can be done with a wet emery cloth. If emery cloth is ineffective, use an 80 to 100 grit aluminum oxide coated paper. Abrasive cloth or paper will result in a very faint grinding away of the floor surface. |
| C. Penetrated stains: | Stains such as caused by oil, putty, etc., may be removed by scouring with a cleanser and then soaking floor overnight, if need be, with a commercial bleach such as Lincio, etc. |

FIAT PRODUCTS® LIMITED ONE YEAR WARRANTY

FIAT Products, LLC offers a limited warranty on FIAT Products to the original Purchaser consumer, both residential and commercial. These products shall be free of defects in material and workmanship for a period of One Year.

Under this warranty FIAT Products will, at its sole discretion, upon receipt of a written claim and proof of purchase, either (1) repair the product, (2) replace the product or any part therein with a FIAT Product of equal or similar type and size, or (3) refund to the consumer the wholesale price of the product received by FIAT Products. If FIAT Products elects to refund the wholesale price to the consumer, FIAT Products shall have no further obligation to its wholesale customer, or any contractor with respect to such product. Goods proven to be defective will be replaced after proper inspection, but no claims for damages incurred or for work done thereon will be allowed. Replacements when supplied will be shipped at no cost to the consumer.

This warranty **does not apply** to local building code compliance. Since local building codes vary considerably, the purchaser of the product should check with a local building or plumbing contractor to ensure local code compliance before installation.

This warranty **will be void** if:

1) the product has been moved from its initial place of installation; 2) if it has been subjected to faulty maintenance, abuse, misuse, accident or other damage; 3) if it was not installed in accordance with FIAT Products instructions; or 4) if it has been modified in a manner inconsistent with the product as shipped by FIAT Products.

This warranty **DOES NOT COVER** any damages caused by the use of non-approved cleaners, improper installations or excessive abuse.

FIAT Products' right to repair or exchange the product under this warranty does not cover any labor or other costs of removal or installation including any costs of any surround material such as tile or marble.

FIAT Products is not responsible for any other incidental or consequential damages attributed to a product defect or to the repair or exchange of a defective product, all of which are expressly excluded from this warranty. (Some states or provinces do not allow the exclusion or limitation of implied warranties, so this exclusion may not apply to you.)

This warranty gives you specific rights. You may have other statutory rights that may vary from state to state or province to province, in which case this warranty does not affect such statutory rights.

In the United States & Canada:

FIAT Products, LLC
4515 E. 139th Street
Grandview, MO 64030
Attention: Customer Care Manager
www.fiatproducts.com

THIS WARRANTY IS NOT TRANSFERABLE FROM ORIGINAL CONSUMER PURCHASER.